	1			2			3	1		5
	1	1		<u> </u>		1		<del>'1</del>	1	
		LIGHTIN NUMBER OF LAMPS		SCHEDULE						
TYP	DESCRIPTION  LED RECESSED DOWNLIGHT WITH 8"	AND WATTAGE	WANGI ACTORER	CATALOG NUMBER  DOM8 LED 1500L 277		APPROVED EQUALS				
A	APERATURE WITH OPEN REFLECTOR	35W LED	GOTHAM	D08 DIM	277					
В	4' T8 STRIP FIXTURE WITH HIGH EFFICIENCY BALLAST AND REFLECTOR	(1) F32 T8	LUMAX	CS13248- EO9U/CSWG4B	277					
С	26W COMPACT FLUORESCENT ELEVATOR PIT WEATHERPROOF FIXTURE	(1) 26W TRT	PHOENIX	VP-W-26CFL-277-GCL-G	277					
D	4' T8 DIRECT/INDIRECT PENDENT MOUNTED FIXTURE WITH HIGH EFFICIENCY ECOSYSTEM DIMMING BALLAST	(1) F32 T8	FOCAL POINT	FV2S-PS-2T8-1C-277- LUT/D-C24-L835-WH-XX	277					
E	1 LAMP RECESSED T8 CHANNEL WITH LOUVER AND HIGH EFFICIENCY BALLAST	(1) F32 T8	LINEAR LIGHTING	WW2-D-1-ET8-277-PBL-R- BW-XX	277					
F	3W LED DESK LIGHT	3W LED	FORUM	TL-3WLED-120V-FINISH BY ARCHITECT	120					
G	(1) 32W COMPACT FLUORESCENT WEATHERPROOF EXTERIOR WEDGE FOR	(1) 32W TRT with Emergency LED		WST 32TRT MD MVOLT 2ELED LPI CBA	277					
F	(2) LAMP T8, 18 CELL PARABOLIC TROFFER WITH		LUMAX	ID 232 24-E09	277					
	HIGH EFFICIENCY ECOSYSTEM BALLAST  RECESSED WALL MOUNTED WEATHERPROOF	4W LED	PHOENIX	SGH-MOR-LED/SG-R-	400					
	LED STEPLIGHT			1LED-AC-WHL-120V-CC 50620300WH-						
M		3W LED	MODULAR	506201009Y-CBA-120V VPF 82-117-LH-277-OP-						
P	2' T8 CEILING MOUNTED DIRECT STAIRWELL FIXTURE	(1) F17 T8	LUMINAIRE LIGHTING	BLK-WET-EMB 50 WITH COLD WEATHER BALLAST						
Q	4' T8 COVE LIGHT MOUNTED IN THE LIGHT SHELF WITH HIGH EFFICIENCY ECOSYSTEM BALLAST	(1) F32 T8	FOCAL POINT	FCVA-26-1T8-1C-277- LUT/R-CV-L835-HW-XX	277					
R	4' T8 PENDANT MOUNTED AIMABLE FIXTURE WIT HIGH EFFICIENCY ECOSYSTEM BALLAST AIMED		FORUM	QUA-S-05-2-CMX8-277- LUT/R-CV-L835-HW-XX'	277					
S	TO THE CENTER OF THE ANGLED CEILING  4' T8 WALL MOUNTED WALL WASHER WITH HIGH EFFICIENCY ECOSYSTEM BALLAST	i (1) F32 T8	FORUM	SADL-05-EXL4'-277-CBA-						
-	COMPACT FLUORESCENT, HORIZONTAL LAMP, LENSED AND WET LOCATION LISTED, 6"			ASYL SG6H-132TRT-EX-CR-	277					
	APERATURE, RECESSED DOWNLIGHT	(1) 32W TRT	SPECTRUM	AR6625CS-PG-WL 4801-30-F-277V-OA-BAL-						
V	33" DIAMETER DECORATIVE PENDANT FIXTURE SINGLE FACE DIE CAST EXIT SIGN WITH BATTER	(4) 13W CFL	WINONA	STD	277					
EX		LED	ISOLITE	LPDC-EM-R-S-AB-UN	277					
EX		LED	ISOLITE	LPDC-EM-R-D-AB-UN	277					
<b>E</b>	Δ . 7	8W (6V) HALOGEN	ISOLITE	ELP-6-27-2-TM-H8W	277					
UN	LED UNDERCABINET LIGHTING WITH 12" JUMPER CABLES AND TERMINATION PLUGS	6W LED	ALKCO	ARIS-11-27-120-PRL-XXX	120					
		SITE LIGH	TING FIXTU	JRE SCHEDUL	E					
TYP	PE DESCRIPTION	NUMBER OF LAMPS AND WATTAGE	MANUFACTURER			APPROVED EQUALS				
EPO	POLE MOUNTED AREA LIGHTING (FORWARD THROW WITH BACKLIGHT SHIELD)	79W LED	BETA LED	BLD-ARE-4B-DA-051-LED- B-UL-XX WITH WHITCO POLE RNAP-20-45-V9-						
EP	POLE MOUNTED AREA LIGHTING (TYPE II DISTRIBUTION)	79W LED	BETA LED	BLD-ARE-T2-DA-051-LED- B-UL-XX WITH WHITCO	277					
	POLE MOUNTED AREA LIGHTING (TYPE II DISTRIBUTION WITH BACKLIGHT SHIELD)	79W LED	BETA LED	POLE RNAP-20-45-V9- BLD-ARE-2B-DA-051-LED- B-UL-XX WITH WHITCO	277					
	BOLLARD WALKWAY LIGHTING WITH			POLE RNAP-20-45-V9- BLD-RBN-T5-NA-010-LED-						600
EB	SCREWS  LED ROPE LIGHT IN CHANNEL - PROVIDE ALL	18W LED	BETA LED	B-UL-XX-PL-TS	277					
LED	POWER SUPPLIES AND ACCESSORIES AS REQUIRED.	LED 5W PER LINEAR FT	. ILIGHT	T-24-X35-S-XX-SC-00	277					r 02
LR		LED 2.1W PER LINEAR FT	T IO LIGHTING	O-06-CAA-2-WM-NR-65- 3K-XX-2	277					e C
U	STAINLESS STEEL AIMABLE LED UPLIGHT WITH SPOT DISTRIBUTION, LINEAR SPREAD LENS, ANI GLARE SHIELD		HYDREL	M9410-SS-12LED-WMW- MVOLT-SP-FLC-XX-LSF- GS-STR-LP-XX						C
										<del>.</del>
										P
										رن ح م
										<b>U</b> ,